



Ideal for the transportation of container, platform, cittern and varied equipment.



**Aura Lift**, engineered to last !

- Heavy-duty frame design with large beveled rear rollers
- Slide-on side rollers and body locks
- Strong sliding jib with nylatron pads
- Works with low pressure hydraulics
- Hydraulic jib lock, with electro-safety switch for a secure operation, in dump, pick up or drop mode
- Built under ANSI-Z245.1-2008 standards and regulations
- Low maintenance and durability

Model Description	DLH - 1214	DLH - 2514	DLH-3518	DLH-3520	DLH-4018	DLH-4020	DLH-4022	DLH-5022	DLH-6022	DLH-6524
<b>GENERAL</b>										
Lift / Dump Capacity	12 000 Lbs	25 000 Lbs	35 000 Lbs	35 000 Lbs	40 000 Lbs	40 000 Lbs	40 000 Lbs	50 000 Lbs	60 000 Lbs	65 000 Lbs
Dry weight	2 385 Lbs	3 100 Lbs	4 400 Lbs	4 825 Lbs	4 800 Lbs	5 200 Lbs	5 375 Lbs	5 675 Lbs	6 350 Lbs	7 575 Lbs
Roll-off Container length *	9 to 14'	9 to 14'	12 to 18'	14 to 20'	12 to 18'	14 to 20'	16 to 22'	16 to 22'	16 to 22'	18 to 24'
Main Cylinders										
Quantity	2	2	2	2	2	2	2	2	2	2
Stroke	48"	48"	60"	72"	60"	72"	80"	80"	80"	88"
Bore	4"	6"	6"	6"	6.5"	6.5"	6.25"	7"	8"	7.5"
Jib Cylinder										
Stroke	28"	28"	40"	48"	40"	48"	52"	52"	52"	52"
Bore	3"	3.5"	4"	4"	4.5"	4.5"	4.5"	5"	5"	5"
Truck Specs										
GVW	18 000 to 25 000Lbs	30 000 to 39 000Lbs	45 000Lbs and up	45 000Lbs and up	45 000Lbs and up	45 000Lbs and up	45 000Lbs and up	60 000 Lbs and up	60 000Lbs and up	60 000Lbs and up
CA	100 to 120"	100 to 120"	130 to 144"	154 to 170"	130 to 144"	154 to 170"	175 to 190"	175 to 190"	175 to 190"	190 to 210"
Clear frame rail	148"	148"	196"	228"	196"	228"	240"	240"	240"	264"
Frame height	45" max	45" max	45" max	45" max	45" max	45" max	45" max	45" max	45" max	45" max



Open top container



Platform

Distributed by :



Providing lifting solutions for every need

[pmindustries.ca](http://pmindustries.ca)

Toll Free: 1-855-656-1689